



17

LIP Bygningsartikler A/S,
Industrivej 16, 5580 Nr. Åby, Danmark

LIP 2K Vådrumssystem Watertight covering kit

DoP No 5001

Release of dangerous substances	No dangerous materials
Vapour permeability	RH 100 → 75 %: $Z_p = 218 \text{ GPa} \cdot \text{s} \cdot \text{m}^2/\text{kg}$ and equivalent $s_d = 42.5 \text{ m}$ RH 94 → 50 %: $Z_p = 236 \text{ GPa} \cdot \text{s} \cdot \text{m}^2/\text{kg}$ and equivalent $s_d = 46.1 \text{ m}$
Water tightness	Watertight according to EN 14891
Crack bridging ability	Assessment category 1: Crack width 0,4 mm
Bond strength	Category 2 ($\geq 0.5 \text{ MPa}$)
Joint bridging ability	Category 2
Water tightness around penetrations	Category 2
Resistance to temperature	Category 2 ($\geq 0.5 \text{ MPa}$)
Resistance to water	Category 2 ($\geq 0.5 \text{ MPa}$)
Resistance to alkalinity	Category 2 ($\geq 0.5 \text{ MPa}$)
Reparability	Reparable
Thickness	Overall thickness 0.62 mm
Applicability	Applicable

ETA-14/0003 of 2023/09/11

Liquid applied watertight covering kit for wet room floors and walls

ETAG 022 part 1

1073-CPR-147-1

