



17

LIP Bygningsartikler A/S,
Industrivej 16, 5580 Nr. Åby, Danmark

LIP VS 30 Watertight covering kit

DoP No 5002

Release of dangerous substances	No dangerous materials
Vapour permeability	RH 100 → 75 %: $Z_p = 220.1 \text{ GPa} \cdot \text{s} \cdot \text{m}^2/\text{kg}$ and equivalent $s_d = 43.0 \text{ m}$ RH 93 → 50 %: $Z_p = 223.6 \text{ GPa} \cdot \text{s} \cdot \text{m}^2/\text{kg}$ and equivalent $s_d = 43.7 \text{ m}$
Water tightness	Watertight according to EN 14891
Crack bridging ability	Assessment category 2: Crack width 0,75 mm
Bond strength	Category 2 ($\geq 0.5 \text{ MPa}$) for concrete substrate Category 1 ($\geq 0.3 \text{ MPa}$) for other materials, as described in clause 2 in ETA-12/0025
Joint bridging ability	Category 2
Water tightness around penetrations	Category 2
Resistance to temperature	Category 2 ($\geq 0.5 \text{ MPa}$)
Resistance to water	Category 2 ($\geq 0.5 \text{ MPa}$)
Resistance to alkalinity	Category 2 ($\geq 0.5 \text{ MPa}$)
Thickness	Minimum thickness of membrane 0.58 mm
Applicability	Applicable

ETA-12/0025 of 2023/09/11

Liquid applied watertight covering kit for wet room floors and walls

1073-CPR-147-2

ETAG 022-1